



## Guest Entertainer – Show Element Request Form

This form is to be utilized to request inclusion of a restricted show element into a Guest Entertainer's onboard performance. Restricted show elements are categorized either by containing a hazardous item or utilizing any rigging. Please refer to the Guest Entertainer Show Elements policy for further information. Multiple requests must be submitted on separate forms.

Act Name:	Mark Nizer
Requestor:	Mark Nizer
Date:	9/5/13
Type of Request: (Indicate Hazardous or Rigging)	Hazardous Material – Fog Fluid Used in Show

Please describe the show element requested to be included in show (include product or item details and specs, previous experience in using the show element, and any contingency plans in place for use):


Request to use Antari FLG Fog Liquid. MSDS form accompanies this form.

-----DO NOT WRITE BELOW THIS LINE-----

### DCL Review and Approval Notes:

Mark Nizer must carry a hard copy of the MSDS form for the Fog Fluid whilst onboard the vessel.  
Mark Nizer must carry a hard copy of this form to accompany the MSDS sheet whilst onboard the vessel.  
Mark Nizer must debark with any remaining Fog Fluid at the end of the sailing.  
Antari FLG Fog Liquid for Mark Nizer cannot be stored onboard by DCL between his sailings.

Approved or Denied

Talent Casting:	
Entertainment Technical:	
Staff Captain (if required):	

Antari Lighting and Effects Ltd.  
No. 8, Lane 231, Nankan Road  
Section 1, Luchu, Tao Yuan  
Taiwan

Tel: (886) 3 322 5829  
Fax: (886) 3 322 7035



Fog from A to Z

sales@antari.com  
www.antari.com

## Material Safety Data Sheet

**EFFECTIVE DATE: 21/03/03**

Antari Lighting and Effects Ltd. provides this MSDS in order to promote consumer understanding of the hazards associated with these products.

The information contained herein should be made available to all Antari employees, agents, contractors, and customers. In turn, these same should make this MSDS available to their employees, agents, contractors and customers. As such, this MSDS shall be included in the master shipping cartons of all products identified below.

### I. IDENTIFICATION

PRODUCT NAMES: "FLG Fog Liquid", "FLR Fog Liquid"

FORMULA: Pure grade propylene glycol, anionic desurfactant (de-ionized water)

### I. PHYSICAL PROPERTIES

APPEARANCE AND ODOR	Pale green, pale red, clear, clear, clear; slight odor
BOILING POINT (760 mm Hg)	210 - 435 F
EVAPORATION RATE (Butyl Acetate=1)	.003 - .006
SPECIFIC GRAVITY (H <sub>2</sub> O=1)	1.075 - 1.085 AT 20 C
SOLUBILITY IN WATER	Completely soluble over 65 F
VAPOR PRESSURE AT 20 C	<.025 - .0245 mm Hg
VAPOR DENSITY (air=1)	3.85 - 3.93

### I. INGREDIENTS

These products are all "water-based" glycol solutions. As such, toxicity is minimal. These products have been shipped internationally for more than 5 years under the Antari name, and are considered "non-hazardous" by most national health and safety regulatory bodies.

Tests conducted by independent laboratories have confirmed the non-hazardous nature of these liquids. The most recent material test returned the following results:

Chromium (Cr)	not detected
Cadmium (Cd)	not detected
Mercury (Hg)	not detected
Arsenic (As)	not detected

### I. FLAMMABILITY DATA

Due to the fact that de-ionized water forms the base for all these solutions, no detectable fire or explosion hazard exists. Flammability is undetermined due to the lack of a flash point or auto-ignition temperature. Extinguishing techniques and/or media should be determined by the fire/safety personnel on site: water, foam, CO<sub>2</sub> and dry chemical media will not cause an adverse chemical or physical reaction with these products.

### I. HEALTH HAZARD DATA

No exposure limits have been determined for these products, nor for any of the ingredients from which

they are formulated.

Swallowing has no adverse effects in low doses. Higher doses may induce nausea and vomiting, but with no long-term toxicity. Inhalation produces no adverse effects when used according to standard practices. Continuous exposure to highly concentrated fog may lead to throat/respiratory tract irritation. Under such conditions, irritation should subside immediately upon moving to an area of low fog concentration. The fog produced by these products will be adequately filtered by any 10 - 20 micron filtration system. Contact with the liquid may cause minimal, temporary irritation to exposed skin areas. Eye contact with the liquid may also cause minimal, temporary irritation. In all cases of contact with the liquid, flushing of the exposed area with water is sufficient. No contra-indications may be determined, as the ingredients have no independently toxicological effects, even when considered combinatively with possible pre-existing physical conditions or dietary/medicinal regimens. Treatment of egregious overexposure may be determined by health personnel, with principal attention given to the control of symptoms and overall clinical status.

#### VI. SPILL AND DISPOSAL PROCEDURES

Spills will result in a slippery film on most surfaces. Flushing with water is a sufficient response. Liquids may be safely disposed according to standard waste disposal methods.

#### VII. REACTIVITY DATA

The liquids described herein are stable formulas. No avoidable reactive risks can be determined through an extrapolation of all possible uses. Exposure to air, heat, water and oxidants poses no risk for reaction. Non-standard combustion of these formulas may produce aldehydes, ketones, carbon dioxide and/or carbon monoxide.

#### I. CONCLUSION

The products covered by this MSDS are not regulated by any international regulating bodies, including the WHMIS. As such, they may be classified as non-hazardous. In view of the above MSDS, the most critical special information concerns protecting employees from irritation which may accompany long-term exposure to the products. They should be able to avoid repeated contact with skin, eyes and/or clothing. Rubber or otherwise coated gloves and eye protection should be worn when handling large volumes or quantities of these products.